

PRODUCT CARD



ALUMINIUM END STRIP

DESCRIPTION

Mounting profiles in high-grade anodised aluminium, designed in shape and dimensions for Rocko Tiles. The profiles have concealed guide profiles for easy installation. Since the concealed guide elements are not perforated, they effectively compensate for any possible curvature of the wall, allowing for more secure adhesion to the substrate. In addition, their robust construction guarantees stability and durability, making them the ideal solution for any finishing project. By choosing our profiles, you ensure easier installation and an aesthetically pleasing finish to your space.

MATERIAL

ANODISED ALUMINIUM

Hydro REDUXA brand aluminium is used in the production of the assembly profiles, which uses renewable energy from water (hydropower), wind and sun in the production of aluminium, making aluminium cleaner, reducing the carbon footprint per kilogram of aluminium to 4.0, less than a quarter of the global average production.

STOP ALUMINIUM

6060 T66

ANODE THICKNESS

The profiles are manufactured by extrusion and then anodised, resulting in a coating with thicknesses within tolerances: 15+5-3 µm

GENERAL DATA

COLOR:

Black, ~~bronze~~, silver and white anode

LENGTH [mm] : 2800

WIDTH [mm]: 18

HEIGHT [mm]: 6,7

LOGISTICAL DATA

UNIT OF MEASUREMENT: piece

NUMBER OF PACKAGES IN INTERMEDIATE PACKAGE: 1 pack

foil

NET UNIT WEIGHT [KG]: 0,2016

UNIT PACK LENGTH [MM]: 2800

UNIT PACKAGING WIDTH [MM]: 18

HEIGHT OF UNIT PACK [MM]: 6,7