

Wilmar bvba
Kalkenstraat 17
B-9255 Buggenhout



DECLARATION OF PERFORMANCE

NL Hoekprofiel RG
FR Cornière RG
DE Eckwinkel RG
EN Cornerprofile RG

Art. Nr. **150 3,05**

DoP-Nr.: **WIL870030000**



EN 14195

Droogbouw
Parachèvement à sec
Trockenausbau
Drywall



35/35 ms

<http://www.wilmar.be/dop>

Material : DX 51D AZ-150 0,4mm

Initial inspection by origin EN 10215 / 10143

Mechanical traits (average) :

Yield (MPA) Re	331
Tensile (MPA) Rm	389
Elongation (%)	30

Chemical traits (average) :

C	0,05
Mn	0,19
Si	0,01
P	0,09
S	0,005
Al	0,048

Weight/pc 0,402 kg	Pc/Pack 60	Size/Pack 80x140x3050	Weight/Pack 24,16 kg	Pack/Pal 48	Size/Pal 880x1020x3050	Weight/Pal 1159,49 kg
-----------------------	---------------	--------------------------	-------------------------	----------------	---------------------------	--------------------------

Declared performance

length	3050	mm
width	35 x 35	mm
thickness	0,405	mm
weight	0,132	kg/m
aluzinc coating	19,6	µm / side a
	19,3	µm / side b
aluzinc weight	150	gr/m ²

Authorized representative : CEO

Date: 01/08/2024

Signed