

Wilmar bvba  
Kalkenstraat 17  
B-9255 Buggenhout



### DECLARATION OF PERFORMANCE

NL Hoekprofiel RG  
FR Cornière RG  
DE Eckwinkel RG  
EN Cornerprofile RG

Art. Nr. **100 1,2**

DoP-Nr.: **WIL100012000**



**EN 13658-1**

Binnenbepoistering  
Enduit intérieur  
Innenputz  
Inside plastering



27/27 rh 11 ev 35

<http://www.wilmar.be/dop>

Material : DX 51D AZ-150 0,4mm

Initial inspection by origin EN 10215 / 10143

Mechanical traits (average) :

|                  |     |
|------------------|-----|
| Yield (MPA) Re   | 331 |
| Tensile (MPA) Rm | 389 |
| Elongation (%)   | 30  |

Chemical traits (average) :

|    |       |
|----|-------|
| C  | 0,05  |
| Mn | 0,19  |
| Si | 0,01  |
| P  | 0,09  |
| S  | 0,005 |
| Al | 0,048 |

|                       |               |                         |                        |                 |                           |                         |
|-----------------------|---------------|-------------------------|------------------------|-----------------|---------------------------|-------------------------|
| Weight/pc<br>0,211 kg | Pc/Pack<br>20 | Size/Pack<br>60x75x1200 | Weight/Pack<br>4,22 kg | Pack/Pal<br>176 | Size/Pal<br>880x1020x1200 | Weight/Pal<br>743,42 kg |
|-----------------------|---------------|-------------------------|------------------------|-----------------|---------------------------|-------------------------|

Declared performance

|                 |         |                     |
|-----------------|---------|---------------------|
| length          | 1200    | mm                  |
| width           | 27 x 27 | mm                  |
| thickness       | 0,405   | mm                  |
| weight          | 0,176   | kg/m not perforated |
| aluzinc coating | 19,6    | µm / side a         |
|                 | 19,3    | µm / side b         |
| aluzinc weight  | 150     | gr/m <sup>2</sup>   |

Authorized representative : CEO

Date: 01/08/2024

Signed :