

Wilmar bvba
Kalkenstraat 17
B-9255 Buggenhout



DECLARATION OF PERFORMANCE

NL Hoekprofiel RG
FR Cornière RG
DE Eckwinkel RG
EN Cornerprofile RG

Art. Nr. **100 1,5**

DoP-Nr.: **WIL100015000**



EN 13658-1

Binnenbeplevstering
Enduit intérieur
Innenputz
Inside plastering



27/27 rh 11 ev 35

<http://www.wilmar.be/dop>

Material : DX 51D AZ-150 0,4mm

Initial inspection by origin EN 10215 / 10143

Mechanical traits (average) :

Yield (MPA) Re	331
Tensile (MPA) Rm	389
Elongation (%)	30

Chemical traits (average) :

C	0,05
Mn	0,19
Si	0,01
P	0,09
S	0,005
Al	0,048

Weight/pc 0,264 kg	Pc/Pack 20	Size/Pack 60x75x1500	Weight/Pack 5,28 kg	Pack/Pal 176	Size/Pal 880x1020x1500	Weight/Pal 929,28 kg
-----------------------	---------------	-------------------------	------------------------	-----------------	---------------------------	-------------------------

Declared performance

length	1500	mm
width	27 x 27	mm
thickness	0,405	mm
weight	0,176	kg/m not perforated
aluzinc coating	19,6	µm / side a
	19,3	µm / side b
aluzinc weight	150	gr/m ²

Authorized representative : CEO

J.D.

Date: 01/08/2024

Signed :

Joori De Backer