

DECLARATION OF PERFORMANCE

NL Verticaal wandprofiel
FR Profil Mural
DE C-Wandprofil
EN C-Wallprofile


Art. Nr. **CW50 4,0**

DoP-Nr.: **AP805040000**



EN 14195

Metalen onderbouw
Sous structure métallique
Metal unterbau
Metal framing



C50

www.amalpro.be

Material : DX 51D Z-140 0,60mm

Initial inspection by origin EN 10215 / 10143

Fire rating A1 – Corrosion class C2

Mechanical traits (average) :

Yield (MPa) Re	331
Tensile (MPa) Rm	389
Elongation (%)	30

Chemical traits (average) :

C	0,05
Mn	0,19
Si	0,01
P	0,09
S	0,005
Al	0,048

Weight/pc 2,76 kg	Pc/Pack 8	Size/Pack 55x440x4000	Weight/Pack 22,08 kg	Pack/Pal 35	Size/Pal 530x1100x4000	Weight/Pal 772,80 kg
----------------------	--------------	--------------------------	-------------------------	----------------	---------------------------	-------------------------

Declared performance

length	4000	Mm
width	49x50x51	Mm
thickness	0,600	Mm
weight	0,69	kg/m
galva coating	19,1	µm / side a
	18,8	µm / side b
galva weight	140	gr/m ²

Authorized representative : CEO

Date 01/01/2023

Signed :
Tom
Heyvaert

Tom Heyvaert
Hoogveld 11
B -9200 Dendermonde