

PRODUCT CARD



EXTERNAL ALUMINIUM CORNER TRIM

DESCRIPTION

Mounting profiles in high-grade anodised aluminium, designed in shape and dimensions for Rocko Tiles. The profiles have concealed guide profiles for easy installation. Since the concealed guide elements are not perforated, they effectively compensate for any possible curvature of the wall, allowing for more secure adhesion to the substrate. In addition, their robust construction guarantees stability and durability, making them the ideal solution for any finishing project. By choosing our profiles, you ensure easier installation and an aesthetically pleasing finish to your space.

MATERIAL

ANODISED ALUMINIUM

Aluminium from Hydro REDUXA, which uses renewable energy from water (hydropower), wind and the sun in the production of its assembly profiles, is used to make aluminium cleaner, reducing the carbon footprint per kilogram of aluminium to 4.0, less than a quarter of the world's average production.

STOP ALUMINIUM

6060 T66

ANODY THICKNESS

Profiles are manufactured by extrusion and then anodised, resulting in a coating with a thickness within tolerances: 15+5-3 µm

GENERAL DATA

KOLOR:

Anoda czarna, brązowa, srebrny oraz biały

COLOR:

Black, silver and white anode

LENGTH [mm] : 2800

WIDTH [mm]: 17,5

HEIGHT [mm]: 17,5

LOGISTICAL DATA

UNIT OF MEASUREMENT: piece

NUMBER OF PACKAGES IN INTERMEDIATE PACKAGE: 1 pack

foil

NET UNIT WEIGHT [KG]: 0,3444

UNIT PACK LENGTH [MM]: 2800

WIDTH OF UNIT PACK [MM]: 17,5

HEIGHT OF UNIT PACK [MM]: 17,5